

BOYA

BY-DMR7

Shotgun Microphone with Integrated Flash Recorder for DSLR Cameras and Video Cameras

Product Introduction

Product Introduction

DOVA The DAMID is a policy orderised microphone special, designed for DSLR camers and cancerders. The imaginated that incomple pulse years for order ACM-REST (and in any angular data) in control in the ACM-REST (and in any angular data) in control in the ACM-REST (and in any angular data) in control in the ACM-REST (and in any angular data) i

- Camero Dn Cendenser Microphone
 Supercendido paler pick up partem
 Supercendido paler pick up partem
 Records 2-Pal-Micro var audio to a Micro SDHC card
 Elay-6-use menu system and LCD display
 Destanthela Sam obs

Packing List

One BY-DMR7 unit

One pop wind shield

One 3.5mm audio transmission cable
User manual





1. Install two AA batteries and a me

I misal in two Av Datumers and a memory Card.

Installing the battery

1) Slide the battery compartment

2) Insert two pieces of AA batteries. Make sure that the + and - signs match the symbols in the compartment.

3) Replace the battery compartment lid.





Note:

8Y-DMR7 can still work as a microphone even if there is no memory card installed. Please make sure the power is off when you insert or remove the memory card.

3. Plug a headphone to the headphone output to monitor Note: The sound can be monitored only on recording screen and playback screen.

Set the control panel. Please refer to " Control Panel Introduction."



Control Panel Introduction

Control (Fin	-1	On housing Screen	On# 1 youds Solem	(In Male Direct	De Solvereer
Jacobia Dovellen	un +	-	Asymptotics audit	- 1	tot the administra
	rogite 🛶	Selevor sold	Ayrecuse	-	Digital to Enable on Administration (1997)
	w t		fremedor other	Sod to	- Sanday - Change commission stay on SYSTEM SET memo
	Down #	Can asserbein refere	Conservator volume	Scott cover	-Social down -Change parameters stelly an SYSTEM STT regrey
	Cretor	-	Foundati	Empr	Emericanten
Recording Nation		(Sarsjavan) Esprisoniling	Data scopping scoon		
Fower fluttion		Crear Main Name		-	_



4. Audio Path

Audio catast

Headprone cutout

Recording to remove; and

1. Menu Introduction
- FILE: Pines, lyspicis, corete button to browne all recorded files.
FOLDBROST dider name.
REC-607 naws? life name.
REC-607 naws? life name.
Debter Risk-stefact has land gives (lyspicit to right to delaye that its.). The not life is name all lind change if a file is deduced where you leggl to noced a now? life, life this named after the delated the name. Note: Once audio files have been deleted, they cannot be recovered.

• INPUT: Set low out filter. Default setting is low out off.

Icd contrasts Set LCD contrast. Default settling is 3.
Set LCD scene contrast from 1 to 5. In LCD contrast screen,
perse joyarisk upsides no adjust contrast level. Then press
int scenes.

versions revision of RCD/MEP Recorder.
factory rate Resisten the factory settlings.


1. Technical Specificati

•	recumcar specimeatio	113

Polar Pattern	Supercardiold
Seconding Formet	WW. 1650/2461, 24616-4586 Sampling Rate
Frequency Bisparse	SO Hz to 20 kHz
Manimum SPL	0 dB Gain Setting, 1 NHz at 116 THD.
	1000 D Need 110 dB SPL
Signal to Noise Batio	78 d8
Operating Temperature Range	-17°C (\$162.65°) to 52°C (134.675)
Audio Output Impedance	470
Headphore Output Impedance	50
Hog	3.5mm jack plug
Forver	Two AA betteries
Dimensions (Lx HxW)	249 x 50 x 95 mm
Net Weight	140g

output volume revers, and the type of measphones used.							
	Battery Runtime (Hours)						
1Battery Type (AA)	When Recording	Passing Audio Only					
Maline	9	10					
NW/H	11.5	14.5					

3. Frequency Response





Operating Menu
MIRIO SUMMENT

11 ILE 76 (LOCKIO) - MICCOO) wav - Delete File 7 feas No.
21 (MICCO) wav - Delete File 7 feas No.
21 (MICCO) wav - Delete File 7 feas No.
21 (MICCO) wav - Delete File 7 feas No.
21 (MICCO) - MICCOO wav - Delete File 7 feas No.
21 (MICCO) - MICCOO wave - Delete File 7 feas No.
21 (MICCO) - MICCOO wave - Delete File 7 feas No.
25 (MICCO) - MICCOO wave - Delete File 7 feas No.
25 (MICCO) - MICCOO wave - Delete File 7 feas No.
26 (MICCO) - MICCOO wave - Delete File 7 feas No.
26 (MICCO) - MICCOO wave - Delete File 7 feas No.
27 (MICCO) - MICCOO wave - Delete File 7 feas No.
28 (MICCO) - MICCOO wave - Delete File 7 feas No.
29 (MICCO) - Delete File 7 feas No.
20 (MICCO) - Delete File 7 feas No.
20 (MICCO) - Delete File 7 feas No.
20 (MICCO) - Delete File 7 feas No.
21 (MICCO) - Delete File 7 feas No.
22 (MICCO) - Delete File 7 feas No.
23 (MICCO) - Delete File 7 feas No.
24 (MICCO) - Delete File 7 feas No.
25 (MICCO) - Delete File 7 feas No.
26 (MICCO) - Delete F

- SD CARD's total field immore planage, and financial field immore planage, and financial film financial SD card fool case of flades. Homeous SD card fool case of flades. Homeous SD card fool case of flades. A CARD Market Proceedings of flades and flades. A CARD Market Proceedings of flades and flades of flades and flades of flades and flades and flades of flades and flades of flades and flades and flades of flades and flades

New cut on: 8Y-DMR? will fifter audio signal that lower than 2005 to reduce noises.

• REC SETs Set recording parameter.

fillal limit Set maximum supposed time limit. If you set fills limit to
30 minutes, 30 minutes recording will be divisited
into 3 superate wow files. Default setting is 60 minutes,
sample rates 65 minute least. The ligher acting yout, the
ligher audio quality you will get.
Default setting is 68 Minute2 better.

when exported.

Icd backlight: Set background LCD lights. Select LCD backlight on, off or delay 5/10/15/30 seconds.